



Punch

SAFETY DATA SHEET PATENT GLOW

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME PATENT GLOW
PRODUCT NO. WAE02000
APPLICATION Maintains a glossy 'new look' on shoes, boots, bags and belts of patent leather.
SUPPLIER Punch Industries
Wallingstown
Little Island
Co. Cork
Ireland
Tel. 00353 21 500 3330
Fax. 00353 21 435 4392
sds@punchindustries.com
EMERGENCY TELEPHONE 00353 21 500 3330

2 HAZARDS IDENTIFICATION

Extremely flammable.

CLASSIFICATION F+;R12.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
BUTANE	203-448-7	106-97-8	5-10%	F+;R12
NAPHTHA(PETROLEUM),HYDRODESULFURIZED HEAVY; LOW BOILING POINT HYD.	265-185-4	64742-82-1	1-5%	Xn;R65. N;R51/53. R10,R66,R67.
TRIBUTYLPHENOL POLYGLYCOL ETHER 1-7 EO		9046-09-7	< 1%	Xi;R36/38. N;R51/53.
ALCOHOLS, C16-18, ETHOXYLATED (APPROX. 20 EO)		68439-49-6	< 1%	Xn;R22. Xi;R41. N;R50.
SODIUM NITRITE	231-555-9	7632-00-0	< 1%	O,R8 T;R25 N;R50

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

GENERAL INFORMATION

This product is supplied in a 200ml aerosol can.

INHALATION

Move the exposed person to fresh air at once.

INGESTION

Do not induce vomiting. Rinse nose, mouth and throat with water. Get medical attention.

SKIN CONTACT

Wash skin thoroughly with soap and water.

EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials. Do not use water jet as an extinguisher, as this will spread the fire.

PATENT GLOW

PROTECTIVE MEASURES IN FIRE

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

Evacuate area. Provide adequate ventilation. Remove all sources of ignition.

ENVIRONMENTAL PRECAUTIONS

Refer to section 13 for disposal considerations.

SPILL CLEAN UP METHODS

Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Provide good ventilation.

STORAGE PRECAUTIONS

Keep in original container.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
BUTANE	WEL	600 ppm	1450 mg/m ³	750 ppm	1810 mg/m ³	Carc

WEL = Workplace Exposure Limit.

Carc = Capable of causing cancer and/or heritable genetic damage.

RESPIRATORY EQUIPMENT

Use breathing protection only if exposed to concentrations above the Work Exposure Limit.

HAND PROTECTION

Hand protection not required.

EYE PROTECTION

Not relevant.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Foam.
COLOUR	White
ODOUR	Characteristic

10 STABILITY AND REACTIVITY

STABILITY

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid exposure to high temperatures or direct sunlight.

11 TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION

No data recorded.

GENERAL INFORMATION

No specific health warnings noted.

12 ECOLOGICAL INFORMATION

PATENT GLOW

ECOTOXICITY

There are no data on the ecotoxicity of this product.

13 DISPOSAL CONSIDERATIONS

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

14 TRANSPORT INFORMATION



UK ROAD CLASS	2		
PROPER SHIPPING NAME	AEROSOLS		
UN NO. ROAD	1950	UK ROAD PACK GR.	N/A
ADR CLASS NO.	2	ADR CLASS	Class 2: Gases
ADR PACK GROUP	N/A	TUNNEL RESTRICTION CODE	(D)
ADR LABEL NO.	2.1	CEFIC TEC(R) NO.	20G5F
RID CLASS NO.	2	RID PACK GROUP	N/A
UN NO. SEA	1950	IMDG CLASS	2.1
IMDG PACK GR.	N/A	EMS	F-D, S-U
UN NO. AIR	1950	AIR CLASS	2.1
AIR PACK GR.	N/A		

15 REGULATORY INFORMATION

LABELLING



Extremely Flammable

RISK PHRASES

R12 Extremely flammable.

SAFETY PHRASES

S2 Keep out of the reach of children
S16 Keep away from sources of ignition - No smoking.
S51 Use only in well-ventilated areas.
A1 Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
A2 Do not spray on a naked flame or any incandescent material.

DETERGENT LABELLING

5 - < 15% Aliphatic hydrocarbons
< 5% Perfumes
Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE,2-METHYL-2H-ISOTHIAZOL-3-ONE

16 OTHER INFORMATION

REV. NO./REPL. SDS GENERATED	3
DATE	16/09/09
SIGNATURE	Gerry Clancy (Technical Manager)

PATENT GLOW

RISK PHRASES IN FULL

R10	Flammable.
R12	Extremely flammable.
R22	Harmful if swallowed.
R25	Toxic if swallowed.
R36/38	Irritating to eyes and skin.
R41	Risk of serious damage to eyes.
R50	Very toxic to aquatic organisms.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.
R8	Contact with combustible material may cause fire.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.